



Bearing No.	Boundary dimensions				Basic load ratings(kN)		Limiting speeds		Mass Kg
	mm				Dynamic	Static	rpm		
	d	D	B	rsmin	Cr	Cor	Grease	Oil	
21308	40	90	23	1.5	88	90	3,200	4,900	0.705
21308K	40	90	23	1.5	88	90	3,200	4,900	0.694
21308KW33C3	40	90	23	1.5	88	90	3,200	4,900	0.694
21308W33C3	40	90	23	1.5	88	90	3,200	4,900	0.705
21309	45	100	25	1.5	102	106	2,900	4,400	0.927
21309K	45	100	25	1.5	102	106	2,900	4,400	0.912
21309KW33C3	45	100	25	1.5	102	106	2,900	4,400	0.912
21309W33C3	45	100	25	1.5	102	106	2,900	4,400	0.927
21310	50	110	27	2	118	127	2,600	4,000	1.21
21310K	50	110	27	2	118	127	2,600	4,000	1.19
21310KW33C3	50	110	27	2	118	127	2,600	4,000	1.19
21310W33C3	50	110	27	2	118	127	2,600	4,000	1.21
21311	55	120	29	2	145	163	2,400	3,700	1.71

21311K	55	120	29	2	145	163	2,400	3,700	1.69
21311KW33C3	55	120	29	2	145	163	2,400	3,700	1.69
21311W33C3	55	120	29	2	145	163	2,400	3,700	1.71
21312	60	130	31	2.1	167	191	2,200	3,400	2.1
21312K	60	130	31	2.1	167	191	2,200	3,400	2.07
21312KW33C3	60	130	31	2.1	167	191	2,200	3,400	2.07
21312W33C3	60	130	31	2.1	167	191	2,200	3,400	2.1
21313	65	140	33	2.1	194	228	2,000	3,100	2.55
21313K	65	140	33	2.1	194	228	2,000	3,100	2.51
21313KW33C3	65	140	33	2.1	194	228	2,000	3,100	2.51
21313W33C3	65	140	33	2.1	194	228	2,000	3,100	2.55
21314	70	150	35	2.1	220	262	1,900	2,900	3.18
21314K	70	150	35	2.1	220	262	1,900	2,900	3.14
21314KW33C3	70	150	35	2.1	220	262	1,900	2,900	3.14
21314W33C3	70	150	35	2.1	220	262	1,900	2,900	3.18
21315	75	160	37	2.1	239	287	1,800	2,700	3.81
21315K	75	160	37	2.1	239	287	1,800	2,700	3.76
21315KW33C3	75	160	37	2.1	239	287	1,800	2,700	3.76
21315W33C3	75	160	37	2.1	239	287	1,800	2,700	3.81
21316	80	170	39	2.1	260	315	1,700	2,500	4.53
21316K	80	170	39	2.1	260	315	1,700	2,500	4.47
21316KW33C3	80	170	39	2.1	260	315	1,700	2,500	4.47
21316W33C3	80	170	39	2.1	260	315	1,700	2,500	4.53
21317	85	180	41	3	289	355	1,600	2,400	5.35
21317K	85	180	41	3	289	355	1,600	2,400	5.28
21317KW33C3	85	180	41	3	289	355	1,600	2,400	5.28
21317W33C3	85	180	41	3	289	355	1,600	2,400	5.35
21318	90	190	43	3	320	400	1,500	2,300	6.3
21318K	90	190	43	3	320	400	1,500	2,300	6.21
21318KW33C3	90	190	43	3	320	400	1,500	2,300	6.21
21318W33C3	90	190	43	3	320	400	1,500	2,300	6.3
21319	95	200	45	3	335	420	1,400	2,100	7.1
21319K	95	200	45	3	335	420	1,400	2,100	7
21319KW33C3	95	200	45	3	335	420	1,400	2,100	7
21319W33C3	95	200	45	3	335	420	1,400	2,100	7.1

21320	100	215	47	3	370	465	1,300	2,000	8.89
21320K	100	215	47	3	370	465	1,300	2,000	8.78
21320KW33C3	100	215	47	3	370	465	1,300	2,000	8.78
21320W33C3	100	215	47	3	370	465	1,300	2,000	8.89
21322	110	240	50	3	495	615	1,200	1,800	11.2
21322K	110	240	50	3	495	615	1,200	1,800	11.1
21322KW33C3	110	240	50	3	495	615	1,200	1,800	11.1
21322W33C3	110	240	50	3	495	615	1,200	1,800	11.2